


Super high power PERC bifacial solar module

JNBM120-585~605

ENGINEERING DRAWING



MECHANICAL PARAMETERS

Cell (mm)	210*105 PERC
Dimensions (L*W*H) (mm)	2172*1303*35
Weight (kg)	35.0
Cable Cross Section Size (mm ²)	4
No. of Cells & Connections	120(6*20)
No. of Diodes	3
Frame	Anodized Aluminium Alloy
Glass Thickness (mm)	2.0

QUALIFICATION

Temperature Cycling Range (°C)	-40~+85
Max. Series Fuse Rating (A)	35
Max.Wind Load/Max.Snow Load (Pa)	2400/5400
Hot Spot Rate	100% Free
Fire Rating	Class C
Junction Box & Connector Protection Grade	IP68
Bifacial Factor(%)	70±5

TEMPERATURE COEFFICIENTS


Nominal Module Operating Temperature (NMOT)	43±2°C
Temperature Coefficient Voltage (Voc)	-0.29 %/°C
Temperature Coefficient Current (Isc)	0.04 %/°C
Temperature Coefficient Power (Pm)	-0.34 %/°C

ELECTRICAL PARAMETERS

Module Type (1500V DC)	JNBM120-585	JNBM120-590	JNBM120-595	JNBM120-600	JNBM120-605
Max. Power at STC (Pmpp/W)	585	590	595	600	605
Output Tolerance (W)	0+5	0+5	0+5	0+5	0+5
Max. Power Voltage (Vmp/V)	34.00	34.21	34.40	34.61	34.80
Max. Power Current (Imp/A)	17.21	17.25	17.30	17.34	17.39
Open Circuit Voltage (Voc/V)	41.10	41.30	41.50	41.70	41.90
Short Circuit Current (Isc/A)	18.26	18.31	18.36	18.42	18.48
Module Efficiency (%)	20.67	20.85	21.02	21.20	21.38
Backside Power Gain	10%		20%		30%
Max. Power (Pmpp/W)	654.5		714		773.5
Max. Power Voltage (Vmp/V)	34.40		34.40		34.40
Max. Power Current (Imp/A)	19.03		20.76		22.49
Open Circuit Voltage (Voc/V)	41.50		41.50		41.50
Short Circuit Current (Isc/A)	20.20		22.03		23.87
Module Efficiency (%)	23.13		25.23		27.33

*Measurement tolerance: Pmax:±3%; Voc:±3%; Isc: ±5%.

I-V CURVE (595W)



PACKING CONFIGURATION

Pieces Per Pallet	31
Pallets Per Container	18
Pieces Per Container	558

Default

Optional

Connector Type	☐ MC4 Compatible	☐ MC4
Cable Length	☐ 400mm/300mm	☐ Customized
Frame Color	☐ Silver	☐ Black

TUV: IEC/EN 61215, IEC/EN 61730
GB/T 19001-2016/ ISO 9001:2015
GB/T 24001-2016/ ISO 14001:2015
GB/T 45001-2020/ ISO 45001:2018
CNAS-CL01: ISO/IEC 17025:2017

12-year Product materials and workmanship quality warranty

Output power			
The 1st year	The 12th year	The 30th year	
≥98.00%	≥93.05%	≥84.95%	

CAUTION: The electrical parameters in this product datasheet do not refer to only one module. Read safety and installation instructions before using the product. The contents of this specification are for reference only and are subject to change without notice. Jinerger reserves the right of final interpretation.
JNM-20230428-11.0Q © 2023 (1) JINNING CLEAN ENERGY TECHNOLOGY LTD. ALL RIGHTS RESERVED.

JINERGY
JINNING CLEAN ENERGY TECHNOLOGY LTD
JINNING PHOTOVOLTAIC TECHNOLOGY LTD
www.jinergy.com